

Antenna Size	93x11 mm		
Die-Cut Size	100x18 mm (alternative size- 98x15 mm with same inlay)		
ISO Std	ISO/IEC 18000-63 (formerly 6C)		
Chip/Inlay	Impinj m730(other chips on request)/ AD Squarewave ® (Avery Dennison-Smartrac)		
Memory Config	EPC:96~128 bit, USER:0 bit,TID:96-bit (48-bit Serial No)		
Operating Freq Band	860 ~ 960 MHz		
Access & Kill Passwords	Shared (Refer chip data sheet).		
Operating Temp. Range	-40 deg C to +85 deg C		
Will work on Metal?	No		
Adhesive	Strong (>15N) -suitable for vehicle windshield and non-metal asset tagging or std adhesive (10N)		
Max Read Distance	Up to 20 m (on windshield).		
Choice of face material	White PET (clear PET or Paper on request)		
Customized Printing	Possible (pre-printing even on adhesive side)		

We offer this RFID Tag with White Face and Strong Adhesive to suit a number of Industrial applications:

1.File	2.Book	3.Parking (entry/exit)	4.Student	5.Gen Purpose	
Tracking	Tagging		Tracking		
+ many other use cases					

- Performance of the tag on different materials may vary.
- We provide customized printing & encoding as additional services to suit specific applications.
- Proven antenna design & mass-produced inlay.
- Price Range: 6.00 -7.0 INR/pc exW Pune (Courier & GST extra as applicable) (printing, encoding charges extra)

Packing: 1,000 pcs, 2,000 pcs, 3000 pcs Rolls-WEL format.

For Pricing & samples, please contact us at: ravindra@preciselabel.com; +91-9820214031

Note: The antenna picture may differ based on chip & antenna tuning by inlay maker.

