


UHF Asset Tag White Wet (WWET) Inlay: 100x30 mm (Higgs 9)	Antenna  Picture
5 m Read Range on windshield, Large Memory, Strong Adhesive, White Printable PET Face	
Antenna Size	93x19 mm
Die-Cut Size	100x30 mm
ISO Std	ISO/IEC 18000-63 (formerly 6C)
Chip/Inlay	Alien Higgs9/ G Tag Antenna Design
Memory Config: Total 1024 bit	EPC:96 bit (expandable to 496 bit), User: up to 688 bit, TID:96-bit (48-bit Serial No)
Operating Freq Band	860 ~ 960 MHz (Global Frequency Band).
Access & Kill Passwords	32-bit each.
Operating Temp. Range	-40 deg C to +85 deg C
Will work on Metal?	No
Adhesive	Strong adhesive suitable for vehicle windshield
Read Distance	5-7m (on windshield) (Dependant on Reader).
Transponder face material	White PET (Printable with Resin ribbons on RFID Label Printers).
Customized Printing	Possible (pre-printing even on adhesive side). We also offer TID printing services.

We offer this RFID Tag with White Face and Strong Adhesive to suit a number of Industrial applications besides asset tracking:

Picture of finished tags	1.Windshield Tag (Vehicle Entry/Exit/Parking)	2. Supply Chain/Warehouse Management	3.File Tracking	4.Process Automation
				
+ many other use cases				

- The antenna is tuned to give best performance on Vehicle windshield.
- We provide customized printing & encoding as additional services to suit specific applications.
- Proven antenna design & mass-produced inlay.
- Product Code: **UHF WWET Inlay 100x30 H9 Strong Adhesive.**
- Packing: **1,000 pcs rolls or as per customer order.**

For technical data sheet & pricing, contact us at :ravindra@preciselabel.com; 9820214031



Precise Label and Paper LLP

FACTORY : Gat No. 747 (Part) , Opp. Essar Steel, Sanaswadi, Pune Nagar Road, Pune- 412 208. India.
 Tel. : +91 (2137) 677777, Fax : +91 (2137) 677700. E-mail: bimal@smarttech.co.in